

**ELECTRICALLY CONDUCTIVE CONJUGATE FIBER**

**Patent number:** JP3249212  
**Publication date:** 1991-11-07  
**Inventor:** MATSUI MASAO; TSUTSUMI HIDENOBU  
**Applicant:** KANEBO LTD  
**Classification:**  
- **International:** *D01D5/30; D01F1/09; D01F8/04; D01D5/30; D01F1/02; D01F8/04;* (IPC1-7): D01D5/30; D01F1/09; D01F8/04  
- **European:**  
**Application number:** JP19900040574 19900220  
**Priority number(s):** JP19900040574 19900220

**Report a data error here**

**Abstract of JP3249212**

**PURPOSE:**To obtain the subject fiber having excellent electrical conductivity and whiteness by bonding an electrically conductive layer composed of a specific conductive particle and a thermoplastic polymer to a protecting layer composed of a fiber-forming polymer. **CONSTITUTION:**The objective fiber is composed of (A) an electrically conductive layer composed of (a) electrically conductive particles containing an inorganic compound as a nucleus covered with a metallic layer and having a coating layer of an electrically conductive metallic compound on the surface and (b) a thermoplastic polymer (preferably polyolefin, polyamide, polyester, etc., having a crystallinity of  $\geq 70\%$ ) and (B) a protecting layer composed of a fiber-forming polymer and bonded to the layer A. The metallic compound to form the coating film is preferably tin oxide, zinc oxide, indium oxide, copper iodide, etc.

---

Data supplied from the **esp@cenet** database - Worldwide